

# ACT-2414A ISM 2.4GHz 1U Quad-Channel Digital Receiver

## Features

- The quad-channel receiver in 1U metal chassis has antenna connectors on the rear panel for connecting the external antenna system.
- MIPRO's unique control panel equips a graphic OLED, providing a larger field of view without a blind angle.
- Stable digital modulation circuitry. 12 channels of interference-free operation are located in a single frequency band.
- Dual tuner true diversity receiving ensures long-distance reception and eliminates signal drop-out.
- Effectively avoids the RF interference from UHF communication products.



## Specifications

Channel	Dual
Chassis	EIA Standard 1U metal case
Antenna	Detachable, rear panel
Frequency Range	ISM 2.4 GHz band (2,400~2,483.5 MHz)
Preset Frequencies	12
Receiving Mode	Dual-tuner true diversity receiving. ACT Sync channel set-up
Sample Rate	24-bit / 44.1 kHz
Frequency Response	20 Hz ~ 20 kHz
Latency	< 4.0 ms
Dynamic Range	> 117 dBA
Output Connectors	Balanced XLR & Unbalanced Ø 6.3 mm, -10 ~ +20 dB adjustable range.
Power Supply	External 100~240V AC switching power supply
Dimensions	420 × 44 × 162 mm (W×H×D)
Weight	Approx. 1.6 kg
Note	Refer to the actual product in the event of product discrepancy.