

SHOW PA Multiplex Amplifier 150 Watts Public Address 100/70v Line

TP-TA-1121



This SHOW public address amplifier is perfect for use in super-markets, churches, convention halls, footy clubs and schools. High performance, excellent sound quality and hassle-free operation make this amplifier an ideal choice for installations.

SHOW is a well represented brand in the public address arena. They offer products ranging from entry level PA to professional level PA, their ergonomic and user-friendly designs reflect through their large range of products consisting of; processors, PA speakers, megaphones, amplifiers and wireless speaker systems. With more than 20 years experience in the Public address field you can rest assured that your investment in a SHOW product will have great performance, excellent sound quality and impeccable reliability.

Features:

- RMS 120W / MAX 150W
- 4 Balanced combo inputs / MIC sensitivity selectable and switchable 24V DC phantom supply for 120W model
- 1 Aux (RCA) stereo input, 4 stage line sensitivity selectable
- 1 PRE out
- 1 MAIN in
- 1 REC. out
- Priority function of input 1 over other inputs, activated microphone (voice priority) with adjustable
- Treble and bass controls
- Outputs for low impedance and constant voltage speaker
- Power supply in AC 115V / 230V switchable, DC 24V
- LED output level indicator

Specifications:

- Power Output (at 4 Ω): RMS 60W / MAX 120W
- Frequency response: 80Hz-15KHz (± 3 dB);AUX:40Hz-18KHz
- Power supply: AC 115V / 230V 50Hz / 60Hz switchable; DC 24V
- Input / sensitivity: MIC: -(combo inputs) balance 2mV (-55dB)
- AUX: Unbalanced 100mV (-18dB)
- CD: 30mV (-10dB)
- Line: Unbalanced 100mV (-18dB)
- MAIN in: 0dB / 1V
- REC output: 0dB / 1V
- Output (Ω): COM 8 Ω
- Output (V): 70V, 100V
- Controls: 1 Master volume control, 2 Treble / Bass controls; 5 volume controls
- Total Harmonic Distortion: 1%
- S/N ratio (Input 1-4): 65dB
- AUX in: 75dB
- MAIN in: 80dB
- Dimensions: 430x262x88mm (WxDxH)
- Weight (Approx.): 10 kg